Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



Jeffcat TD-33A catalyst CAS107-16-9 Huntsman

Jeffcat TD-33A is a tertiary amine catalyst used in the production of polyurethane foam. It is a 33% solution of triethylenediamine (TEDA) in dipropylene glycol. Jeffcat TD-33A is compatible with most common polyols and isocyanate systems. It is also compatible with water-based systems.

Physical and chemical properties:

Properties	value
Looks	Clear colorless liquid
Scent	Mild, amine-like
рН	10.5
Specific Gravity	1.03
Flash Point	110 degrees Fahrenheit
Spontaneous combustion	450 degrees Fahrenheit

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



temperature	
Solubility	Miscible with water, alcohols and ketones
Stable	Stabilize at room temperature

CAS number

107-16-9

Molecular Formula

C12H23N3

Molecular weight

197.34 g/mole

Apply

Jeffcat TD-33A is used to catalyze the reaction of polyols and isocyanates to produce polyurethane foam. It is used in a variety of applications including:

Rigid foam

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

NEUITOP

Soft foam

Spray foam

Forming foam

Styrofoam



Precautions for use

Jeffcat TD-33A is a flammable liquid and should be handled with care. It should be stored in a cool, dry place away from heat sources and open flames. Jeffcat TD-33A can irritate skin and eyes. If it comes into contact with skin or eyes, wash the affected area with soap and water immediately. If inhaled, move to fresh air and seek medical attention if breathing becomes difficult.

Consult the safety data sheet for more information about Jeffcat TD-33A.

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Technical Indicators

Shelf Life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com