Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



NT CAT EA-102 catalyst CAS106317-60-3 Newtopchem

NT CAT EA-102 is a balanced catalyst that improves foam fluidity and skin quality, especially in low-density applications. It is a clear, colorless liquid with a mild odor. NT CAT EA-102 is a 33% solution of triethylenediamine (TEDA) in monoethylene glycol (MEG).

NT CAT EA-102 is used in a variety of polyurethane applications, including:

Soft foams		
Hard foam		
Isocyanurate foam		
Elastomer		
Paint		
Adhesive		
Sealer		

NT CAT EA-102 is a versatile and effective polyurethane catalyst. It is available from a variety of suppliers.

Here are some safety precautions to take when using the NT CAT EA-102:

Wear gloves, goggles, and a respirator when handling the NT CAT EA-102.

Technical Indicators



- Avoid contact with skin and eyes.
- Do not inhale vapors or fumes.
- Keep away from heat sources and open flames.
- Store in a cool, dry place.
- Dispose of it properly according to local regulations.

Here are some of the features of the NT CAT EA-102:

- Molecular formula: C6H14N4
- Molecular weight: 154.2 g/mol
- Appearance: clear colorless liquid
- Smell: mild
- Density: 1.03 g/cm³
- Boiling point: 195 ° C
- Flash point: 100°F
- Solubility: Soluble in water, ethanol, dichloromethane
- Stability: Stable under normal conditions
- Danger: corrosive, flammable and explosive

Here are some of the benefits of using NT CAT EA-102:

Technical Indicators

- Improved foam liquidity
- Improved skin quality
- Effective in low density applications
- Versatile and effective
- Available from a variety of suppliers

Here are some disadvantages of using the NT CAT EA-102:

- Possible corrosion of metal
- Combustible
- Can explode
- Should be handled with care

Overall, NT CAT EA-102 is a versatile and effective polyurethane catalyst. It is available from a variety of suppliers and is relatively inexpensive. However, it is important to understand the dangers associated with NT CAT EA-102 and take the appropriate safety precautions when handling it.







Here are more detailed information about NT CAT EA-102:

NT CAT EA-102 is a strong base that can irritate the skin and eyes. If it comes into contact with your skin or eyes, flush the affected area with water for at least 15 minutes and seek immediate medical attention.

NT CAT EA-102 is flammable and can irritate the respiratory tract if inhaled. If you inhale vapors or fumes, move to fresh air and seek medical attention if you develop any symptoms.

NT CAT EA-102 can be explosive if mixed with other chemicals, such as aldehydes, ketones, and carboxylic acids. Do not mix NT CAT EA-102 with any other chemicals unless you are sure they are compatible.

Technical Indicators

If you are using NT CAT EA-102, be sure to follow all safety precautions. Wear gloves,

goggles, and a respirator when handling the NT CAT EA-102. Avoid contact with skin

and eyes. Do not inhale vapors or fumes. Keep away from heat sources and open

flames. Store in a cool, dry place. Dispose of it properly according to local regulations.

Here is some additional information about the NT CAT EA-102:

NT CAT EA-102 is a registered trademark of Evonik Industries.

NT CAT EA-102 is available in a variety of sizes and concentrations.

NT CAT EA-102 is a cost-effective polyurethane catalyst.

NT CAT EA-102 is a safe and effective catalyst when used properly.

Here are some additional safety precautions to take when using NT CAT EA-102:

Always wear gloves and goggles when handling the NT CAT EA-102.

Avoid skin contact with NT CAT EA-102. If skin contact occurs, wash the affected

area with soap and water immediately.

Avoid inhaling vapors or fumes from NT CAT EA-102. If you do inhale vapor or

fog, move to fresh air and seek medical attention if you develop any symptoms.

Do not mix NT CAT EA-102 with other chemicals unless you are sure they are

compatible.

Keep NT CAT EA-102 out of reach of children and pets.

Technical Indicators

Store the NT CAT EA-102 in a cool, dry place.

Dispose of the NT CAT EA-102 properly according to local regulations.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical and business Tel: Manager Wu 183 0190 3156

Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



Technical support and business contacts E-mail: in	fo@newtopchem.com
----------------------------------------------------	-------------------