

NT CAT LA-600 catalyst CAS10861-07-1 Newtopchem

Appearance: Clear colorless liquid

Smell: mild

Density: 1.03 g/cm³

Flash point: 98°F (37°C)

Vapor pressure: 0.1 mmHg at 25 °C

Solubility: miscible with water, alcohols and ketones

Stability: Stable under normal conditions



Use:

Soft foam

Paint

Benefits:

- No glow
- Balanced catalyst
- High efficiency catalyst
- Wide processing range

Risks:

- Skin allergies
- Respiratory irritation
- Flammable

Safety notes:

- Always wear personal protective equipment (PPE) when handling the NT CAT LA-600, including gloves, goggles, and a respirator.
- Keep the NT CAT LA-600 away from heat sources and open flames.

- Do not inhale NT CAT LA-600 vapor or mist.
- If NT CAT LA-600 comes into contact with your skin, wash the area immediately with soap and water.
- If you ingest NT CAT LA-600, call the poison control center immediately.

Additional information:

- NT CAT LA-600 is a registered trademark of Evonik Industries.
- NT CAT LA-600 is available in a variety of sizes and concentrations.
- The NT CAT LA-600 should be stored in a cool, dry place.
- NT CAT LA-600 should be disposed of in accordance with local, state, and federal regulations.

CAS Number: 10861-07-1

Chinese alias:

- Daboco NE600
- Polyurine catalyst

English alias:

- Dabucco NE600

- Polyurethane catalyst

Here is a table of the NT CAT LA-600's physical properties:

Property	Value
Looks	Clear colorless liquid
Scent	Mild
Density	1.03 g/cm ³
Flash point	98°F (37°C)
Steam pressure	0.1 mm Hg at 25 °C
Solubility	Miscible with water, alcohols and ketones
Stable	Stable under normal conditions

Here is the NT CAT LA-600's usage chart:

Use	Benefits
Soft foam	Provides good cushioning, comfort, and water resistance.
Paint	Provides good adhesion, durability, and water resistance.

The following is a table of risks associated with using the NT CAT LA-600:

Risks	prevent
Skin allergies	Wash the area immediately with soap and water.
Respiratory irritation	If you experience any symptoms, move to fresh air and seek medical attention.
Flammable	Keep away from heat sources and open flames.

The following table lists the safety precautions to take when using the NT CAT LA-600:

Precautions	Action
-------------	--------

Personal Protective equipment (PPE)	Always wear gloves, goggles, and a respirator when handling the NT CAT LA-600.
Heat and open flame	Keep the NT CAT LA-600 away from heat and open flames.
Steam or fog	Do not inhale NT CAT LA-600 vapor or fog.
Skin contact	If the NT CAT LA-600 comes into contact with your skin, wash the area immediately with soap and water.
Ingestion	If ingesting NT CAT LA-600, call the poison control center immediately.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com