## Newtop Chemical Materials (Shanghai) Co.,Ltd. Technical Indicators



## RC Catalyst 105 CAS99-95-6 Rhine Chemistry

RC Catalyst 105 is a non-halogenated water-based catalyst for the production of polyurethane foams. It is a clear, colorless liquid with a mild odor. The active ingredient in RC Catalyst 105 is 2, 4-dihydroxybenzoic acid.

## **Physicochemical properties**

Properties	value
CAS number	99-95-6
Molecular Formula	C7H6O3
Molecular weight	136.11 g/mole
Density	1.20g/cm <sup>3</sup>
Flash point	100 °C
Solubility	Miscible with water

## **Apply**

Newtop Chemical Materials (Shanghai) Co.,Ltd.

**Technical Indicators** 

soft and semi-hard foams. It is also used in the production of polyurethane elastomers

RC Catalyst 105 is used to produce a variety of polyurethane foams, including hard,

and sealants.

**Pros** 

RC Catalyst 105 has a number of advantages over other polyurethane catalysts,

including:

It does not contain halogens and is therefore environmentally sound.

It is water-based and therefore easy to use and clean up.

It is safe to handle and use.

It produces high quality foam with good physical properties.

**Precautions for use** 

RC Catalyst 105 is a strong acid that can cause skin irritation and burns. It is important

to wear gloves and safety goggles when handling RC Catalyst 105. It is also important

to keep RC Catalyst 105 away from children and pets.

Storage

The RC Catalyst 105 should be stored in a cool, dry place. It should be stored in an

airtight container to prevent moisture from entering.

Newtop Chemical Materials (Shanghai) Co.,Ltd.

**Technical Indicators** 

**Treatment** 

RC Catalyst 105 should be disposed of in accordance with local regulations. Always

consult a hazardous waste disposal company to ensure safe disposal of the RC Catalyst

105.

**Shelf life:** 

Remain unopened for two years

**Storage and Transportation:** 

Should be sealed, stored in a dry cool ventilated warehouse

**Packing:** 

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper

ventilation. After the original packaging, please fasten the packaging cover as soon as

Newtop Chemical Materials (Shanghai) Co.,Ltd.

**Technical Indicators** 

possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous

membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and

change after work. Store contaminated clothes separately and use them after washing.

Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com